

CLAIMS:

1. (Previously amended). A projection display system, comprising:
 - (a) a light source that provides light;
 - (b) a polarizing device that receives said light;
 - (c) at least one polarizing beam splitter that receives said light that has previously been received by said polarizing device;
 - (d) at least one generator for generating an image that receives light that has previously been received by said polarizing beam splitter;
 - (e) a projection source for projecting said image;
 - (f) a color component rotator optically located between said polarizing device and said projection source, wherein at least a portion of said light passes through said color component rotator, wherein said color component rotator changes the polarization state of a first wavelength range of said light incident thereon while being free from changing the polarization state of a second wavelength range of light incident thereon; and
 - (g) wherein said light of said first wavelength range and said second wavelength range are transmitted through said system simultaneously.
2. (Original). The projection display system of claim 1 wherein said color component rotator is between said polarizing beamsplitter and said light source.
3. (Original). The projection display system of claim 1 further comprising a second color component rotator.
4. (Original). The projection display system of claim 1 further comprising a second liquid crystal display panel for generating a second image.
5. (Canceled).

6. (Original). The projection display system of claim 4 further comprising a third liquid crystal display panel for generating a third image.

7. (Canceled).

8. (Original) The projection display system of claim 1 wherein said polarizing device is a polarization converter.

9. (Canceled).

10. (Original) The projection display system of claim 1 further comprising a dichroic filter.

11. (Original) The projection display system of claim 1 wherein said color component rotator is located between a polarizer and an analyzer.

12. (Canceled).

13. (Original). The projection display system of claim 1 wherein light from said light source is separated into three color components.

14. (Original). The projection display system of claim 13 wherein said three color components are red, blue and green.

15-16. (Canceled).

17. (Previously Amended). A projection display system, comprising:
- (a) a light source that provides light;
 - (b) a polarization converter that receives said light;
 - (c) at least two polarizing beam splitters that receive said light that has previously been received by said polarizing device;
 - (d) at least three image generators that receive said light that has previously been received by at least one of said polarizing beam splitters, each for generating a respective image;
 - (e) a projection source for projecting said images; and
 - (f) at least one wavelength-selective color component rotator wherein at least a portion of said light passes through said color component rotator—and wherein at least one wavelength range of said light passing through said rotator is rotated while at least one other wavelength range of said light passing through said rotator is not rotated.
18. (Original). The projection display system of claim 17 wherein one of said color component rotators is between one of said polarizing beamsplitters and said polarization converter.
19. (Original). The projection display system of claim 17 wherein said polarization converter comprises a fly's eye lens plate and prism array.
20. (Original). The projection display system of claim 17 further comprising a dichroic filter and a crossed dichroic prism.
- 21-23. (Canceled).
24. (Original). The projection display system of claim 17 wherein said color component rotators are located between a polarizer and an analyzer.

25. (Original). The projection display system of claim 17 further comprising a pair of dichroic filters.

26. (Original). The projection display system of claim 25 wherein said pair of dichroic filters define at least two color channels, and one of said polarizing beamsplitters is located in one of said color channels and the other of said polarizing beamsplitters is located in the other of said color channels.

27. (Original). The projection display system of claim 17 wherein said projection source projects a projected image formed from three color components.

28. (Original). The projection display system of claim 27 wherein said three color components are red, blue and green.

29-31. (Canceled).

32. (Withdrawn). A method for displaying an image, comprising:

- (a) providing light comprised of a first color component, a second color component, and a third color component;
- (b) converting said light to a single polarization state;
- (c) separating said first color component from said second and third color components while said first, second, and third color components are in the same beam;
- (d) changing said polarization state of said second color component relative to said third color component while said second and third color components are within the same beam;
- (e) separating said second color component from said third color component while said second and third color components are within the same beam;
- (f) generating respective images from each of said first, second, and third color components separated from one another into different beams; and
- (g) projecting said images.

33. (Withdrawn). The method of claim 33 wherein said first, second and third color components are green, blue and red respectively.

34. (Withdrawn). The method of claim 32 wherein said polarization states of said second and third color components are matched again before generating said image from said second color component.

35. (Canceled).

36. (Withdrawn). The method of claim 32 wherein said first color component is separated from said second and third color component using a dichroic filter.

37. (Withdrawn). The method of claim 36 wherein said second color component is separated from said third color component using a polarizing beamsplitter.

38. (Withdrawn). The method of claim 32 wherein said polarization state of said second color component is changed using a color component rotator.

39. (Withdrawn). The method of claim 32 wherein said first, second and third color components are reflected onto respective liquid crystal display panels to generate said images.

40. (Withdrawn). The method of claim 39 wherein said first, second and third color components are reflected onto respective liquid crystal display panels using only two polarizing beamsplitters.

41. (Canceled).

42. (Withdrawn). The method of claim 32 further comprising the step of changing the polarization state of said first color component before generating said image from said first color component.

43. (Withdrawn). The method of claim 42 further comprising the step of changing the polarization state of said first color component again after generating said image from said first color component.